





























motion and Lighting Management sensors for 1 circuit

selection chart

MOTION SENSORS

AREAS WITHOUT NATURAL LIGHT	INSTALLATION		
	Ceiling 	Wall 	
		Surface mounting ⁽²⁾	Flush-mounting ⁽¹⁾
PASSAGEWAY			
Hall/lobby Stairways/hallways Storage areas/technical areas	 0488 03 ⁽¹⁾	 0489 11	 5740 47 ⁽¹⁾ /5740 34 ⁽⁴⁾ - Without neutral
OUTDOOR AND DAMP AREAS			
Indoor/external car park Indoor entrance areas	 0697 40/0697 80	 0489 31 Fixed head  0697 40 Directional head	-























LIGHTING MANAGEMENT SENSORS

AREAS WITH NATURAL LIGHT		Automatic On-Off Checking permanently the presence and daylight level		
WORK AREAS				
Individual office/small room	 0488 00/0488 04 ⁽³⁾	 0489 14	 5740 49/5740 31 ⁽¹⁾	
Open plan office/classroom/ meeting room	 0488 06 ⁽¹⁾ /0488 09	 0489 16 ⁽³⁾	 5740 49/5740 31 ⁽¹⁾	
PASSAGEWAY				
Hall/lobby Stairways/hallways	 0488 07 ⁽¹⁾ /0488 08 ⁽¹⁾	 0489 17 ⁽³⁾	 5740 47 ⁽¹⁾ /5740 34 ⁽⁴⁾ - Without neutral	
Hallways Very long areas	 0488 17 ⁽¹⁾	 0489 17 ⁽³⁾	 5740 47 ⁽¹⁾ /5740 34 ⁽⁴⁾ - Without neutral	
High ceiling areas (gymnasium, storage areas...)	 0489 32 (Flush-mounting)	 0489 33		
Restrooms, bathrooms Dressing room	 0488 04 ⁽³⁾	 0489 16 ⁽³⁾	 5740 47 ⁽¹⁾ /5740 34 ⁽⁴⁾ - Without neutral	
OUTDOOR & DAMP AREAS				
Indoor/outdoor car park lot Indoor entrance areas	 0489 32  0489 33 Directional head	 0489 33 Directional head		




1: Surface mounting box option - 2: corner mounting option - 3: 1 lighting output + 1 fan output - 4: Dedicated retrofit solution

Lighting Management sensors and room controllers for multiple circuits control

selection chart

CHOOSE THE SENSOR	Automatic On-Off Checking permanently the presence and the light level		
	INSTALLATION		
	Ceiling 	Wall 	
		Surface mounting	Flush-mounting
WORK AREAS			
Individual office Classroom	 0488 22 	 0488 23 	 5740 48 
PASSAGEWAY			
Restrooms, changing rooms...	 0488 20 	 0488 24 	 5740 46 
Hallways Very long areas	 0488 20 	 0488 25 	-
High ceiling areas (gymnasium, storage area...)	-	 0488 25 	-
OUTDOOR & DAMP AREAS			
Car park lot, cellar, laboratory, test room, changing room IP 55	-	 0488 30 	-

AND THE OUTPUTS TO BE MANAGED

	ON-OFF	DIMMING		
		DALI	1-10 V	Halogen  - Incandescent  - Dimmable LEDs ⁽¹⁾ 
1 lighting circuit in the same room	0488 50	0488 51	0488 52	0488 45
1 lighting circuit + fan output in the same room	0488 50	0488 51	0488 52	-
2 lighting circuits in the same room	0488 50	0488 51	0488 52	0488 45
2 lighting circuits + 1 fan output in the same room	-	0488 51	-	-
2 lighting circuits (2 inputs, 2 outputs) in 2 rooms	0488 41	-	0488 42 (1000 VA)	0488 45
4 lighting circuits (4 inputs, 4 outputs) in 4 rooms	0488 43	0488 44 (max. 32 ballasts)	0488 43	-
2 lighting circuits + 1 blind output + 1 fan output (4 inputs, 4 outputs) in the same room	0488 47	-	0488 47	-

1: Refer to the load table in the data sheet available online in the e-catalogue (

Note: some commercially available dimmable LEDs are not compatible)